MECHANISMS AND BEHAVIORS IN COMPLEX SYSTEMS WITH GROUP INTERACTIONS

Thomas Robiglio

IT:U Interdisciplinary Transformation University Austria DNDS, Central European University Inverse Complexity Lab

February 28, 2025

Some references

- Battiston, F. *et al.* The physics of higher-order interactions in complex systems. *Nature Physics* **17**, 1093–1098 (2021)
- Rosas, F. E. *et al.* Disentangling high-order mechanisms and high-order behaviours in complex systems. *Nature Physics* **18**, 476–477 (2022)
- Robiglio, T. et al. Synergistic signatures of group mechanisms in higher-order systems. arXiv preprint arXiv:2401.11588 (2024)
- Peel, L. *et al.* Statistical inference links data and theory in network science. *Nature Communications* **13**, 6794 (2022)



${\rm Mechanisms}$

Structural and dynamical rules controlling the causal evolution of the system.

Examples:

$$H = -\sum_{i \neq j} J_{ij} s_i s_j, \quad P\left(s_i^t \to s_i^{t+1}\right) = \dots$$
$$\rho_i^{t+1} = \rho_i^t + \mu [1 - \rho_i^t] - \rho_i^t \left\{ 1 - \prod_j \left[1 - \beta A_{ij} (1 - \rho_j^t) \right] \right\}$$
$$\dot{\theta}_i = \omega_i + \lambda \sum_j A_{ij} \sin(\theta_j - \theta_i)$$

Behaviors

Measurable observables quantifying statistical interdependencies between units.

Examples:

- Correlations
- Mutual information
- Autocorrelation
- Transfer entropy
- ...

Beyond pairwise?

HIGHER-ORDER MECHANISMS

Explicit representations of group interactions^{1,2}:



¹Battiston, F. et al. Networks beyond pairwise interactions: Structure and dynamics. Physics reports 874, 1-92 (2020).

²Battiston, F. et al. The physics of higher-order interactions in complex systems. Nature Physics 17, 1093-1098 (2021).

HIGHER-ORDER MECHANISMS

Higher-order interactions lead to explosive phenomena:



HIGHER-ORDER BEHAVIORS

Information two r.v. X_1 and X_2 contain a third r.v. Y^3 :



³Williams, P. L. & Beer, R. D. Nonnegative decomposition of multivariate information. arXiv preprint arXiv:1004.2515 (2010).

HIGHER-ORDER BEHAVIORS

$$\begin{array}{c} X_{2} \\ X_{1} \\ TC(\mathbf{X}^{n}) \equiv \sum_{j=1}^{n} \mathcal{H}(X_{j}) - \mathcal{H}(\mathbf{X}^{n}) \rightarrow \text{Collective constraints} \\ DTC(\mathbf{X}^{n}) \equiv \mathcal{H}(\mathbf{X}^{n}) - \sum_{j=1}^{n} \mathcal{H}(X_{j} | \mathbf{X}_{-j}^{n}) \rightarrow \text{Shared randomness} \end{array}$$

O-information: $\Omega(\mathbf{X}^n) \equiv \mathrm{TC}(\mathbf{X}^n) - \mathrm{DTC}(\mathbf{X}^n)$

Intuitively⁴:

$$\Omega(\mathbf{X}^n) > 0 \rightarrow \text{Redundancy dominates}$$

 $\Omega(\mathbf{X}^n) < 0 \rightarrow \text{Synergy dominates}$

⁴Rosas, F. E. *et al.* Quantifying high-order interdependencies via multivariate extensions of the mutual information. *Physical Review E* 100, 032305 (2019).

LOW-ORDER MECHANISM

LOW-ORDER BEHAVIOR

Correlations, MI, Granger caus., etc.

HIGHER-ORDER MECHANISM

HIGHER-ORDER BEHAVIOR

TC, O-info, etc.

LOW-ORDER MECHANISM

LOW-ORDER BEHAVIOR

Correlations, MI, Granger caus., etc.

HIGHER-ORDER MECHANISM



HIGHER-ORDER BEHAVIOR

TC, O-info, etc.





What to do?

- 1. Clarify definitions
- 2. Systematic exploration
- 3. Full mapping?

The hard task



The "easy" task



The "easy" task - models





$$H = -J_0 \sum_{i=1}^{N} S^i - \sum_{\ell=1}^{\ell_{\max}} J_\ell \sum_{\{\sigma \in \mathcal{K} : |\sigma|=\ell\}} \left[2\bigotimes_{i \in \sigma} S^i - 1 \right]$$

(ii) Simplicial contagion model⁶



Pairwise infection rate: β_1 Group infection rate: β_2 Recovery rate: μ

⁵Robiglio, T. et al. Higher-order Ising model on hypergraphs. arXiv preprint arXiv:2411.19618 (2024).

⁶Iacopini, I. et al. Simplicial models of social contagion. Nature communications 10, 2485 (2019).

THE "EASY" TASK - BEHAVIOR OBSERVABLE

Generalize O-information to time-lagged correlations⁷:

- 1. Considering *n* variables $\mathbf{X} = (X_1, ..., X_n)$ on which we compute the O-information Ω_n ,
- 2. Add a new variable Y,
- 3. Compute the variation of O-information:

$$\Delta_n = \Omega_{n+1}(\mathbf{X}, Y) - \Omega_n(\mathbf{X})$$

4. Condition of the past of Y:

$$d\Omega_n(Y; \mathbf{X}) \equiv (1 - n) \mathcal{I}(Y; \mathbf{X} | Y_0) + \sum_{j=1}^n \mathcal{I}(Y; \mathbf{X}_{-j} | Y_0)$$

We define **total** dynamical O-information:

$$d\Omega_n^{\text{tot.}}(\mathbf{X}) \equiv \sum_{j=1}^n d\Omega_{n-1}(X_j; \mathbf{X}_{-j})$$

⁷Stramaglia, S. *et al.* Quantifying dynamical high-order interdependencies from the o-information: an application to neural spiking dynamics. *Frontiers in Physiology* 11, 595736 (2021).

Synergistic signatures



INSUFFICIENCY OF LOW-ORDER METRICS



Transfer entropy: $\mathcal{T}(X; Y) \equiv \mathcal{I}(X_t, Y_{t+1}|Y_t)$ Statistical distance: $d(P_2, P_3) = \frac{1}{2} \sum_{x \in \chi} |P_2(x) - P_3(x)|$

LANDSCAPE



Pairwise Ising: $J_1^{\text{cr.}} = T/\langle k_1 \rangle$

Contagion: pairwise $\lambda_1^{\text{cr.}} = 1$, disc. transition $\lambda_1 = 2\sqrt{\lambda_2} - \lambda_2$

DOWNSTREAM TASKS

Given: pairwise structure⁸ and $\langle k_2 \rangle$ **Task:** find the true higher-order interactions



⁸Young, J.-G. et al. Hypergraph reconstruction from network data. Communications Physics 4, 135 (2021).

SUMMARY

- Don't mix behaviors and mechanisms
- Emergence of synergistic signatures of higher-order mechanisms
- Higher-order signatures are invisible to low-order observables
- These signatures are a "weak" emergent phenomena
- Can be useful for downstream tasks (e.g. detection)

General picture:

Intricate relation between mechanisms and behaviors.

What can be done better?

Address the hard task



How do we actually compute the observables?

$$\mathcal{H}(X) = -\sum_{x \in \Sigma} p(x) \log p(x)$$

Given a set of M observations $\{x_i\} \in \{0, 1\}^M$:

$$\mathcal{H}(X) = -\sum_{x \in \{0,1\}} p_x \log p_x \text{ where } p_x = \frac{1}{M} \sum_{i=1}^M \delta_{x_i,x_i}$$

.



INVERSE PROBLEM⁹



⁹Peel, L. et al. Statistical inference links data and theory in network science. Nature Communications 13, 6794 (2022).

BAYESIAN APPROACH

We can only make hypotheses and evaluate to which extent the data supports them.

$$P(\mathbf{A}|\mathbf{D}) = \frac{P(\mathbf{D}|\mathbf{A})P(\mathbf{A})}{P(\mathbf{D})}$$

or if we have a model for the dynamics¹⁰ with parameters $\{d\}$:

$$P(A, \{d\}|\mathbf{D}) = \frac{P(\mathbf{D}|\mathbf{A}, \{d\})P(\mathbf{A}, \{d\})}{P(\mathbf{D})}$$

¹⁰Peixoto, T. P. Network reconstruction and community detection from dynamics. Physical review letters 123, 128301 (2019).

WRAPPING UP

- "Network" language can be too intuitive \rightarrow fix terminology behaviors/mechanisms
- Relation between synergistic behavior and group mechanisms
- No "model-free" analysis



Matteo Neri



Cosimo Agostinelli



Davide Coppes



Federico Battiston



Maxime Lucas



Giovanni Petri



Tiago P. Peixoto